HK39C

Handheld Digital Multimeter



OVERVIEW

A compact auto-ranging handheld digital multimeter with true RMS measurement for electrical maintenance and field service. NCV and live-wire detection, a built-in flashlight and a backlit display cover panel and workshop checks.

FEATURES

- True RMS measurement
- Continuity check and diode test
- NCV (non-contact voltage) detection
- Live wire detection
- Battery test (1.5 V / 9 V)
- Data hold
- LCD backlight and built-in flashlight
- Unit icon display
- Low battery indication
- Auto power off

SPECIFICATIONS

Display	2000 counts · LCD 42.5 × 26 mm
DC voltage	200 mV / 2 V / 20 V / 200 V / 600 V · ±(0.8 % + 5)
AC voltage	2 V / 20 V / 200 V / 600 V · ±(1.2 % + 5)
Resistance	200 Ω / 2 kΩ / 20 kΩ / 200 kΩ / 2 MΩ / 20 MΩ · ±(1.2 % + 8)
Temperature (°C)	−20 °C to 1000 °C · ±(2.0 % + 3)
Temperature (°F)	−4 °F to 1832 °F · ±(3.0 % + 3)
Range select	Auto range
Safety category	CAT III 600 V
Battery	1.5 V (AAA) × 2

Product size	119 × 65 × 30 mm
Product weight	130 g

Specifications are as published in the product technical data sheet. Instruments are quoted per enquiry — contact VEROMET for pricing and availability.